

Doc #: SDS005 Rev. 0 Rev. V. Meeks - 8/24/2016

SECTION 1 - IDENTIFICATION

Product Name:PET-G Shrink FilmProduct Grade:Bonpet ® 7MChemical Name:Co-Polyester Film

CAS Number: None

Product Use: Packaging, labeling, etc. - This product is considered an article under OSHA Hazard

Communication Standard (29 CFR 1910.1200 (b)(6)(v)).

Manufacturer: Bonset America Corporation
Manufacturer Address: 6107 Corporate Park Drive
Browns Summit, NC 27214

Drowns Summit, NC

Emergency Phone #: 336-375-0234

SECTION 2 - HAZARDS IDENTIFICATION

Bonpet ® PET-G Shrink Film is expected to be a low hazard for usual industrial or commercial handling and is not considered a hazardous chemical per OSHA's Hazard Communication Standard.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| Components | CAS Registry No. | Approx. Wt % |
|-------------------------------|------------------|--------------|
| Co-polyester | 25640-14-6 | < 95% |
| Non-Hazardous Voiding Polymer | Trade Secret | < 30% |
| Silica | 14808-60-7 | < 3% |

SECTION 4 - FIRST-AID MEASURES

Description of necessary first aid measures

Inhalation: Remove to fresh air. Get medical attention if symptoms persist.

Skin Contact: *Under normal temperature - Remove affected clothing and shoes. Wash skin thoroughly with

soap and water. Get medical attention if symptoms occur.

*With molten material - Remove affected clothing and shoes. If burned by contact with molten material, cool as quickly as possible. Do not peel material from skin. Get medical attention

immediately.

Eye Contact: Any material that contacts the eye should be flushed out immediately with lukewarm water,

holding eyelids apart, for 15 minutes. Get medical attention if symptoms persist.

Ingestion: Do NOT induce vomiting. Get medical attention. Material is not expected to be absorbed from

the gastrointestinal tract.

SECTION 5 - FIRE-FIGHTING MEASURES

| Extinguishing media | Water spray and dry chemical |
|--|---|
| Specific hazards arising from the chemical | Powdered material may form explosive dust / air mixtures. |

Print Date: 8/25/2016

Page: 1 of 4



Doc #: SDS005 Rev. 0 Rev. V. Meeks - 8/24/2016

| Special protective equipment and precautions for fire- | Wear self-contained breathing apparatus and protective |
|--|--|
| fighters | clothing. |

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedure

Use appropriate personal protective equipment when cleaning up releases. Refer to Section 8.

Environmental precautions

Protect sewers and waterways. May act as sewer/waterway obstruction.

Methods and materials for containment and cleaning up

Stop leak; contain spill; obstruct exit to sewers, waterways and sources of ignition. Collect into containers.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling

- Use appropriate gloves and PPE when handling material. See Section 8.
- Avoid breathing in vapors during processing or dust when material is reground.

Conditions for safe storage, including any incompatibilities

- Store in a cool, dry area. Avoid excessive heat or cold. Avoid excessive humidity or dryness.
- Avoid storage near ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

| ACGIH Threshold Limit | Value (TLV): | N/A | |
|-----------------------|-------------------------|-----|--|
| OSHA (USA) Permissib | e Exposure Limit (PEL): | N/A | |

Engineering Control

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems or respiratory protection may be needed in special circumstances, such as poorly ventilated spaces, mechanical generation of dusts, heating, drying etc.

Personal Protective Equipment

| Respiratory Protection: | If engineering controls do not maintain airborne concentration to an acceptable level, an approved respirator must be worn. Respiratory type - Dust: If respirators are used, a program should be instituted to assure compliance with OSHA standard 29 CFR 1910.134. |
|--|---|
| Eye Protection: Wear safety glasses when handling. It is a good industrial hygiene practice to minimize ey contact. | |
| It'irin Ductoctions | Wear appropriate protective gloves for handling. It is a good industrial hygiene practice to minimize skin contact. When material is heated, wear gloves to protect against thermal burns. |

Print Date: 8/25/2016

Page: 2 of 4



Doc #: SDS005 Rev. 0 Rev. V. Meeks - 8/24/2016

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| Form/Appearance: | Solid / Sheet Film | Vapor Pressure (mmHg): | Solid |
|------------------|-----------------------------|----------------------------------|-------|
| Color: | White Opaque / Matte Finish | Boiling Point: | Solid |
| Odor: | Plastic | Solubility in Water: | N/A |
| pH: | N/A | Vapor Density: | N/A |
| Melting Point: | > 219°C | Autoignition Temperature: | N/A |
| Flash Point: | N/A | | |

SECTION 10 - STABILITY AND REACTIVITY

Reactivity Hazardous polymerization will not occur.

Chemical stability Stable under normal temperatures and pressures.

Conditions to avoid Temperatures greater than 219°C.

Incompatible materials

Hazardous decomposition

products

Ingestion

Material can react with strong oxidizing agents.

None under normal temperatures and pressures.

SECTION 11 - TOXICOLOGICAL INFORMATION

Routes of Exposure

Skin/Eye Contact Expected to be a low hazard under normal handling, temperatures, and pressures. Molten

polymer can cause thermal burns.

Inhalation Expected to be a low hazard under normal handling, temperatures and pressures. Reground

material can create dust particulates. Heating material to a molten state can create vapors.

If ingested, get medical attention. Not expected during normal processing. Expected to be a low

ingestion hazard.

Toxicity No Information Available

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity

This product is not expected to be harmful to aquatic life or the environment as it is a stable

solid and insoluble in water.

Persistence and degradability
Bioaccumulative potential
Mobility in soil:
No Information Available
No Information Available
No Information Available
No Information Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or reuse product when applicable. Dispose of in accordance with federal, state and local regulations through recycling, incineration or landfill.

SECTION 14 - TRANSPORT INFORMATION

Transportation Requirements Not a DOT Hazardous Material.

Print Date: 8/25/2016

Page: 3 of 4



Doc #: SDS005 Rev. 0 Rev. V. Meeks - 8/24/2016

SECTION 15 - REGULATORY INFORMATION

US Federal

TSCA All Components are listed on TSCA Inventory.

SARA Section 313

This product does not contain any chemicals subject to the reporting requirements of SARA

and 40 CFR Part 372.

Other Regulations For more information about compliances and regulations, please refer to our **Product**

Regulatory Information Sheet for PETG Films - PRIS0002, available upon request.

SECTION 16 - OTHER INFORMATION

| NFPA Rating | HMIS Rating |
|----------------|----------------|
| Health 1 | Health 0 |
| Flammability 1 | Flammability 1 |
| Reactivity 0 | Reactivity 0 |

Revision Information

Document No. SDS005

Created By Victoria Meeks Date Created 8/24/2016

Last Revision Date 8/24/2016 Revision No. 0

Revised By Victoria Meeks

The information set forth herein has been gathered from standard reference materials and/or Bonset America Corporation test data. This data, to the best knowledge and belief of Bonset America Corporation, is accurate and reliable. Such information is offered solely for you sonsideration, investigation, and verification. Since the actual use by other is beyond our control, no guarantee, expressed or implied is made by Bonset America Corporation, as to the effects of such use, the results to be obtained, or the safety and toxicity of the product, nor does Bonset America Corporation assume any liability arising out of the use, by others, of the product referred to herein.

Print Date: 8/25/2016

Page: 4 of 4