

Doc #: SDS006 Rev. 0 Rev. V. Meeks - 8/24/2016

#### **SECTION 1 - IDENTIFICATION**

**Product Name:** PET-G Shrink Film

**Product Grade:**Bonpet ® 7G **Chemical Name:**Co-Polyester Film

CAS Number: None

**Product Use:** Packaging, labeling, etc. - This product is considered an article under OSHA Hazard

Communication Standard (29 CFR 1910.1200 (b)(6)(v)).

Manufacturer: Bonset America Corporation

Manufacturer Address: 6107 Corporate Park Drive

Browns Summit, NC 27214

**Emergency Phone #:** 336-375-0234

#### **SECTION 2 - HAZARDS IDENTIFICATION**

Bonpet ® PET-G Shrink Film is expected to be a low hazard for usual industrial or commercial handling and is not considered a hazardous chemical per OSHA's Hazard Communication Standard.

# **SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

Components	CAS Registry No.	Approx. Wt %
Co-polyester	25640-14-6	< 95%
Polyester	29154-49-2	< 30%
Titanium Dioxide	13463-67-7	< 10%
Silica	14808-60-7	< 3%

#### **SECTION 4 - FIRST-AID MEASURES**

# Description of necessary first aid measures

Inhalation: Remove to fresh air. Get medical attention if symptoms persist.

Skin Contact: \*Under normal temperature - Remove affected clothing and shoes. Wash skin thoroughly with

soap and water. Get medical attention if symptoms occur.

\*With molten material - Remove affected clothing and shoes. If burned by contact with molten material, cool as quickly as possible. Do not peel material from skin. Get medical attention

immediately.

Eye Contact: Any material that contacts the eye should be flushed out immediately with lukewarm water,

holding eyelids apart, for 15 minutes. Get medical attention if symptoms persist.

Ingestion: Do NOT induce vomiting. Get medical attention. Material is not expected to be absorbed from the

gastrointestinal tract.

#### **SECTION 5 - FIRE-FIGHTING MEASURES**

Extinguishing media	Water spray and dry chemical

Print Date: 8/25/2016

Page: 1 of 4



Doc #: SDS006 Rev. 0 Rev. V. Meeks - 8/24/2016

Specific hazards arising from the chemical	Powdered material may form explosive dust / air mixtures.
Special protective equipment and precautions for fire-	Wear self-contained breathing apparatus and protective
fighters	clothing.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedure

Use appropriate personal protective equipment when cleaning up releases. Refer to Section 8.

# **Environmental precautions**

Protect sewers and waterways. May act as sewer/waterway obstruction.

# Methods and materials for containment and cleaning up

Stop leak; contain spill; obstruct exit to sewers, waterways and sources of ignition. Collect into containers.

#### **SECTION 7 - HANDLING AND STORAGE**

#### **Precautions for safe handling**

- Use appropriate gloves and PPE when handling material. See Section 8.
- Avoid breathing in vapors during processing or dust when material is reground.

# Conditions for safe storage, including any incompatibilities

- Store in a cool, dry area. Avoid excessive heat or cold. Avoid excessive humidity or dryness.
- Avoid storage near ignition sources.

#### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

# **Exposure Limits**

ACGIH Threshold Limit Value (TLV):	N/A
OSHA (USA) Permissible Exposure Limit (PEL):	N/A

# **Engineering Control**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems or respiratory protection may be needed in special circumstances, such as poorly ventilated spaces, mechanical generation of dusts, heating, drying etc.

#### Personal Protective Equipment

	<del></del>
Respiratory Protection:	If engineering controls do not maintain airborne concentration to an acceptable level, an approved respirator must be worn. Respiratory type - Dust: If respirators are used, a program should be instituted to assure compliance with OSHA standard 29 CFR 1910.134.
Eye Protection: Wear safety glasses when handling. It is a good industrial hygiene practice to minimize e contact.	
Skin Protection:	Wear appropriate protective gloves for handling. It is a good industrial hygiene practice to minimize skin contact. When material is heated, wear gloves to protect against thermal burns.

Print Date: 8/25/2016

Page: 2 of 4



Doc #: SDS006 Rev. 0 Rev. V. Meeks - 8/24/2016

# **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form/Appearance:	Solid / Sheet Film	Vapor Pressure (mmHg):	Solid
Color:	White Slight Translucence / Gl	oss Boiling Point:	Solid
Odor:	Plastic	Solubility in Water:	N/A
pH:	N/A	Vapor Density:	N/A
Melting Point:	> 219°C	<b>Autoignition Temperature:</b>	N/A
Flash Point:	N/A		

# **SECTION 10 - STABILITY AND REACTIVITY**

**Reactivity** Hazardous polymerization will not occur.

**Chemical stability** Stable under normal temperatures and pressures.

**Conditions to avoid** Temperatures greater than 219°C.

**Incompatible materials** Material can react with strong oxidizing agents.

**Hazardous decomposition** 

products

None under normal temperatures and pressures.

### **SECTION 11 - TOXICOLOGICAL INFORMATION**

**Routes of Exposure** 

Ingestion

Skin/Eye Contact Expected to be a low hazard under normal handling, temperatures, and pressures. Molten polymer

can cause thermal burns.

Inhalation Expected to be a low hazard under normal handling, temperatures and pressures. Reground

material can create dust particulates. Heating material to a molten state can create vapors.

If ingested, get medical attention. Not expected during normal processing. Expected to be a low

ingestion hazard.

**Toxicity** No Information Available

# **SECTION 12 - ECOLOGICAL INFORMATION**

Ecotoxicity

This product is not expected to be harmful to aquatic life or the environment as it is a stable solid

and insoluble in water.

Persistence and degradability No Information Available Bioaccumulative potential No Information Available Mobility in soil: No Information Available Other adverse effects: No Information Available

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Recycle or reuse product when applicable. Dispose of in accordance with federal, state and local regulations through recycling, incineration or landfill.

#### **SECTION 14 - TRANSPORT INFORMATION**

**Transportation Requirements** Not a DOT Hazardous Material.

Print Date: 8/25/2016

Page: 3 of 4



Doc #: SDS006 Rev. 0 Rev. V. Meeks - 8/24/2016

# **SECTION 15 - REGULATORY INFORMATION**

**US Federal** 

TSCA All Components are listed on TSCA Inventory.

SARA Section 313

This product does not contain any chemicals subject to the reporting requirements of SARA and

40 CFR Part 372.

Other Regulations

For more information about compliances and regulations, please refer to our **Product Regulatory** 

Information Sheet for PETG Films - PRIS0002, available upon request.

#### **SECTION 16 - OTHER INFORMATION**

NFPA Rating	HMIS Rating
Health 1	Health 0
Flammability 1	Flammability 1
Reactivity 0	Reactivity 0

**Revision Information** 

**Document No.** SDS006

Created By Victoria Meeks Date Created 8/24/2016

Last Revision Date 8/24/2016 Revision No. 0

**Revised By** Victoria Meeks

The information set forth herein has been gathered from standard reference materials and/or Bonset America Corporation test data. This data, to the best knowledge and belief of Bonset America Corporation, is accurate and reliable. Such information is offered solely for you sonsideration, investigation, and verification. Since the actual use by other is beyond our control, no guarantee, expressed or implied is made by Bonset America Corporation, as to the effects of such use, the results to be obtained, or the safety and toxicity of the product, nor does Bonset America Corporation assume any liability arising out of the use, by others, of the product referred to herein.

Print Date: 8/25/2016

Page: 4 of 4